2

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

- 1 1. (previously amended) A crosspoint switch integrated circuit comprising:
- 2 an array of input ports;
- an array of output ports;
- 4 a switch matrix configured to selectively connect said input ports
- to said output ports for conducting electrical signals therebetween; and
- 6 equalization circuitry coupled to at least partially offset trans-
- 7 mission losses experienced by said electrical signal while external to said
- 8 crosspoint switch integrated circuit, said equalization circultry being
- 9 configured to measure jitter within said electrical signals and to utilize jitter
- 10 measurements as a basis for offsetting said transmission losses, said
- 11 equalization circuitry being responsive to said jitter measurements to
- 12 automatically select levels of equalization.
  - 1 2. (cancelled)
  - 3. (original) The crosspoint switch integrated circuit of claim 1 wherein said
  - 2 equalization circuitry includes a plurality of adjustable equalizers, said
  - 3 adjustable equalizers each having adjustable filtering characteristics within a
  - 4 fixed number of equalization settings.
  - 4. (original) The crosspoint switch integrated circuit of claim 3 wherein each
  - 2 said adjustable equalizer includes a plurality of switchable connections which
  - 3 individually adjust said filtering characteristics when activated.

3

- 1 5. (original) The crosspoint switch integrated circuit of claim 4 wherein each
- 2 said switchable connection includes a switch, at least some of said switchable
- 3 connections including at least one component which significantly affects said
- 4 filtering characteristics when said switchable connections are individually
- 5 activated.
- 1 6. (original) The crosspoint switch integrated circuit of claim 5 wherein at
- 2 least some of said switchable connections are arranged in electrical parallel
- 3 and said components Include capacitors and resistors.
- 1 7. (original) The crosspoint switch integrated circuit of claim 5 wherein at
- 2 least some of said switchable connections are arranged in electrical parallel
- 3 and said components include an Inductor and a resistor.
- 8. (original) The crosspoint switch integrated circuit of claim 5 wherein said
- 2 switches are transistors and said components include at least some of
- 3 resistors, capacitors, or inductors.
- 1 9. (original) The crosspoint switch integrated circuit of claim 4 wherein
- 2 adjustable equalizers are coupled to said input ports in one-to-one
- 3 correspondence.
- 1 10-18. (cancelled)

4

- 1 19. (currently amended) A method of providing equalization for a crosspoint
- 2 switch formed on an integrated circuit chip switch comprising:
- determining signal characteristics related to signal transmissions
- 4 via each of a plurality of ports of said crosspoint switch, including providing
- on-chip measurements of jitter of electrical signals, wherein said jitter is
- 6 induced by off-chip conditions; and
- 7 setting equalization circuitry housed within said crosspoint
- 8 switch such that each said port has filtering characteristics tailored on a
- 9 basis of said signal characteristics for said signal transmissions via said
- each port, said setting being automated and being at least partially based on
- 11 said on-chip measurements of jitter.
- 1 20. (previously presented) The method of claim 19 wherein said step of
- 2 setting includes selectively activating and deactivating switching devices
- 3 which introduce parallel connections of resistances and capacitances within
- 4 said equalization circuitry, said equalization circuitry being a plurality of
- 5 adjustable equalization circuits.
- 1 21. (previously presented) The method of claim 19 wherein said step of
- 2 setting includes selectively activating and deactivating switching devices
- 3 which introduce series connections of resistances and inductances within said
- 4 equalization circuits.
- 1 22. (original) The method of claim 19 wherein said step of setting includes
- 2 activating adaptive equalization circuitry.
- 1 23-24. (cancelled)

5

- 1 25. (previously presented) The crosspoint switch integrated circuit of claim 1
- 2 wherein said equalization circuitry includes a multiplexer connected to a jitter
- 3 measurement component for providing said jitter measurements, said
- 4 multiplexer being connected to receive said electrical signals from each of
- 5 said input ports and being operatively associated with said jitter measurement
- 6 component to enable said jitter measurements on a port-by-port basis.
- 1 26. (previously presented) The crosspoint switch integrated circuit of
- 2 claim 25 wherein said jitter measurement component includes a phase-locked
- 3 loop for tracking data transactions within said electrical signals, said jitter
- 4 measurement component further including a voltage-controlled oscillator
- 5 connected to be responsive to operations of said phase-locked loop.
- 1 27. (previously presented) The crosspoint switch integrated circuit of claim 1
- 2 wherein said equalization circuitry is configured to recurringly execute said
- 3 jitter measurements and recurringly execute responsive selection of said
- 4 levels of equalization for individual said input ports, thereby enabling said
- 5 levels of equalization to track variations in said transmission losses.